

AMENDMENTS TO THE CLAIMS

Pursuant to 37 C.F.R. § 1.121 the following listing of claims will replace all prior versions, and listings, of claims in the application.

1 – 2. (Canceled)

3. (withdrawn) A method for establishing a common key for a group of at least three subscribers, the method comprising:

generating by each subscriber T_i of the at least three subscribers a respective message $N_i = (g^{z_i} \bmod p)$ from a publicly known element g of large order of a publicly known mathematical group G and a respective random number z_i and sending the respective message from the respective subscriber to all other subscribers T_j of the at least three subscribers, each respective random number z_i being selected or generated by the respective subscriber T_i ;

generating by each subscriber T_i a transmission key k^i from the messages N_j received from the other subscribers $T_j, j \neq i$, and the respective random number z_i according to $k^i := N_j^{z_i} = (g^{z_j})^{z_i}$;

sending by each subscriber T_i the respective random number z_i in encrypted form to all other subscribers T_j by generating the message M_{ij} according to $M_{ij} := E(k^j, z_i)$, $E(k^j, z_i)$ being a symmetrical encryption algorithm in which the data record z_i is encrypted with the transmission key k^j ; and

determining a common key k by each subscriber T_i using the respective random number z_i and the random numbers $z_j, j \neq i$, received from the other subscribers according to

$k := f(z_1, \dots, z_n)$,

f being a symmetrical function which is invariant under a permutation of its arguments.

4. (withdrawn) The method as recited in claim 3 wherein the transmission key k^i is known to subscriber T_j according to $k^i = k^j$.

5. (Currently Amended) A method for establishing a common key for a group of at least three subscribers for transmitting messages over a communication channel, the method comprising the steps of:

generating, by each subscriber T_i , a respective message $N_i = (g^{z_i} \text{ mod } p)$ $N_j = (g^{z_j} \text{ mod } p)$ from a publicly known element g of large order of a publicly known mathematical group G and a respective random number $[[z_i]]$ $z_j, j = 1$ to n , where n is the number of subscribers in the group of at least three subscribers; and

sending the respective message, by each subscriber except a predetermined first subscriber T_1 of the at least three subscribers, to the first subscriber T_1 ; ~~each respective random number $[[z_i]]$ being selected or generated by the respective subscriber $[[T_i]]$;~~

encrypting, by the first subscriber T_1 , the received messages N_j of the other subscribers $T_j, j \neq 1$, with the random number z_1 to form a respective transmission key k^{ij} for each subscriber $T_j, j \neq 1$;

sending, by the first subscriber T_1 , the random number z_1 to all other subscribers $T_j, j \neq 1$ in encrypted form by generating a message M_{ij} according to $M_{ij} := E(k^{ij}, z_1)$, $E(k^{ij}, z_1)$ being a symmetrical encryption algorithm in which the random number z_1 is encrypted with the transmission key k^{ij} ; and

determining a common key k , by each subscriber $[[T_i]]$ T_i , ~~using the values N_i and $N_j, j \neq i$, and the random number z_1 sent by the first subscriber T_1 in encrypted form using an assignment $k :=$~~ $h(z_1, g^{z_2}, \dots, g^{z_n}), h(x_1, x_2, \dots, x_n)$ being a function which is symmetrical in the arguments x_2, \dots, x_n , the common key k being useable for transmitting messages over a communication channel.

9. (New) The method according to claim 7, wherein the length of p is at least 1024 bits.
10. (New) The method according to claim 7, wherein g has a multiplicative order of at least 2^{160} .
11. (New) The method according to claim 7 wherein the transmission key is known to a respective subscriber T_j according to $k^{1j} = k^{j1}$.
12. (New) The method according to claim 7, wherein $h(z1, g^{z2}, \dots, g^{zn}) = g^{z1*z1} * g^{z2*z1} * \dots * g^{zn*z1}$.
13. (New) A method for establishing a common key for a group of subscribers for encryption and decryption of messages, the method comprising the steps of:
- each of the subscribers T_j generating a respective random number z_j , where j goes from 1 to n and n is the number of subscribers in the group of subscribers;
 - each of the subscribers T_j storing the respective random number z_j in a respective memory;
 - each of the subscribers T_j generating a respective first message $N_j = (g^{z_j} \bmod p)$ from a publicly known element g of large order of a publicly known mathematical group G ;
 - each of the subscribers $T_j, j \neq 1$, sending the respective first message to a first subscriber T_1 ;
 - the first subscriber T_1 storing each of the received first messages in a memory;
 - the first subscriber T_1 computing a transmission key $k^{1j} = N_j^{z1} \bmod p$ for each of the other subscribers $T_j, j \neq 1$, based on the received respective first message $N_j, j \neq 1$;

the first subscriber T_1 encrypting a second message $M_{1j} := E(k^{1j}, z_1)$ for each of the other subscribers $T_j, j \neq 1$, where $E(k^{1j}, z_1)$ is a symmetrical encryption algorithm in which z_1 is encrypted with the transmission key k^{1j} ;

the first subscriber T_1 sending the encrypted second message M_{1j} to each of the respective other subscribers $T_j, j \neq 1$;

each of the respective other subscribers $T_j, j \neq 1$, storing the received encrypted second message in the respective memory; and

each of the subscribers T_j computing a common key k according to an assignment $k := h(z_1, g^{z_2}, \dots, g^{z_n})$, where $h(x_1, x_2, \dots, x_n)$ is a symmetrical function, and n is the number of subscribers in the group.

14. (New) The method according to claim 13, wherein a maximum number of transmission rounds required is two.

15. (New) The method according to claim 13, further comprising the steps of:

one of the respective subscribers T_i using the computed common key k to encrypt a third message;

the one of the respective subscribers T_i transmitting the encrypted third message to each of the other respective subscribers;

each of the other respective subscribers $T_j, j \neq i$ decrypting the received encrypted third message using the computed common k .